

KR630 Ramp Stacker

Automatically sorts and stacks cards, envelopes, booklets, magazines and more.

- Runs in-line with most addressing and bindery systems.
- Built-in divert system
- Straightforward operator interface
- Minimal set-up time

**Built
Kirk-Rudy
tough!**



KR Kirk-Rudy, Inc.

Ph: 770.427.4203

www.kirkrud.com

KR630

RAMP STACKER

Automatically sorts and stacks cards, envelopes, booklets, magazines and more.

** General Specifications

PHYSICAL

English

Metric

Length	96"	2438.4 mm
Width	56"	1422.4 mm
Height	72"	1828.8 mm
Infeed Height	34" (adjustable)	863.6 mm
Outfeed Height	32.5"	825.5 mm
Outfeed Conveyor Length	24"	609.6 mm

ELECTRICAL REQUIREMENTS

Voltage	Amp	Phase	Hz
120 VAC	20	1	60

AIR REQUIREMENTS

40 psi at 1/2 cfm

PRODUCT SPECIFICATIONS

Minimum	6" x 8"	(152.4 x 203.2 mm)
Maximum	12" x 15"	(304.8 x 381 mm)
Thickness	Minimum Single Sheet	Maximum .625" (15.8 mm)
Stack Height	Minimum 1 piece	Maximum 9" (228.6 mm)

OPERATING SPEEDS

Maximum	Up to 400 ft/min
Stack Cycle Speed	50 stacks per minute

Note: Speeds are dependent on material being fed

FEATURES:

- Runs in-line with most addressing and bindery systems
- Built-in pneumatic divert system
- PLC control system
- Compact design
- Straightforward operator interface
- Designed for minimal set up time

OPTIONS:

- Left or right stacker outfeed conveyor
- Batch counter
- Hydraulic lift kit
- Reduced or extended outfeed conveyor

** Specifications subject to change without notice.

