

KR725

Bag Feeder

FEED STACKED FLAT BAGS

Smooth transfer on every feed!



The KR725 feeds one bag at a time for printing and/or labeling.

- Vacuum conveyor
- Pick and place feed
- Suction cup mechanism
- Accomodates uneven stacks
- Automatic stack loader



KR725

Bag Feeder

** General Specifications

Physical	English	Metric
Length	136"	345.4 cm
Width	46"	116.8 cm
Height	61"	154.9 cm

Electrical Requirements

Voltage	Amp	Phase	Hz
120 VAC	20	1	60

Product Capacity

Width	Min 11" (279.4 mm)	Max 16.50" (419.1mm)
Length	Min 18" (457.2 mm)	Max 30.75" (781.05 mm)

* Additional product sizes possible. Contact Kirk-Rudy, Inc. for information.

Operating Speeds

Maximum	Up to 30 bags/minute
---------	----------------------

Note: Speeds are dependent on material being fed

Features & Benefits

- Pick and place mechanism is designed to flex and accommodate bags that do not stack evenly.
- Venturi vacuum generators for suction cups to reduce power consumption and noise level
- Rugged construction
- The touch screen interface provides a way to change machine settings, monitor the status of the machine, display faults, and allow manual operations.

Options

- KR535HD Labelmaster for applying labels
- KR inkjet systems for printing
- Gantry to mount OEM labeling heads
- Angled catch tray to collect bags
- Shingling conveyor to collect bags



**Specifications subject to change without notice.