

KR725 Bag Feeder

Feed Stacked Flat Bags

Designed to feed one bag at a time from a stack onto a vacuum conveyor for printing and/or labeling. The pick and place suction cup mechanism removes the top bag off a stack that is a maximum of 7" tall and accomodates bags that do not stack evenly.

- Flexible suction cup mechanism for difficult bags
- Automatic stack loader
- Touch screen interface

Engineered for high production environments



KR725

Bag Feeder

** General Specifications

PHYSICAL

	English	Metric
Length	165.75"	421 cm
Width	77.75"	197.5 cm
Height (tabletop)	33.25"	84.5 cm

ELECTRICAL REQUIREMENTS

Voltage	Amp	Phase	Hz
220 VAC	20	1	60/50

FEATURES and BENEFITS

- Flexible pick and place mechanism feeds bags that do not stack evenly
- Venturi vacuum generators for suction cups reduces power consumption and noise level
- Touch screen interface for machine operation
- Rugged construction

OPTIONS

- Gantry for mounting labeling heads
- KR Inkjet printing systems
- KR Labelmaster
- Angled catch tray
- Shingling conveyer

PRODUCT CAPACITY

Width	Min 7" (177.8 mm)	Max 22" (558.8 mm)
Length	Min 10" (254 mm)	Max 36" (914.4 mm)

* Additional product sizes possible. Contact Kirk-Rudy, Inc. for information.

OPERATING SPEED

Maximum	30-50 bags/minute
---------	-------------------

Note: Speeds are dependent on material being fed

COMPRESSED AIR REQUIREMENTS

80 PSI @ 5 SCFM



Flexible pick and place suction cup mechanism.



KR725 shown with optional gantry mount.

**Specifications subject to change.