

KR840R

Roller Registration

Accurately register a wide range of product efficiently and conveniently. Use with inkjet printing systems, labeling, card attaching, and other lines. Integrated controls allow for easy speed matching, stopping and starting with a Kirk-Rudy base.

**Easily
added to
existing
lines**

- Moveable table
- Right or left hand justified
- Micro adjustments
- Adjustable pinch rollers

- ✓ Heavy duty
- ✓ Portable
- ✓ Easy set-up



KR840R

Roller Registration

Accurately register a wide range of product

FEATURES:

- Justify product right or left
- Hand crank moveable table
- Micro adjustments
- Adjustable pinch rollers
- Easy belt changes

OPTIONS:

- Stand-alone controls
- Wide version available



** General Specifications

Product Capacity

Width	Min 3" (7.6 cm)	Max 17" (43.2 cm)
Length	Min 3" (7.6 cm)	Max 18" (45.7 cm)
Thickness	Min .004" (.18 mm)	Max .25" (6.35 mm)

Operating Speeds

Maximum	Variable to 500 feet per minute
---------	---------------------------------

Note: Speeds are dependent on material being fed

Physical

	English	Metric
Length	24"	61 cm
Width	39.50"	100.3 cm
Height	49.25"	125.1 cm
Weight	250 lbs.	113.4 kg.

Electrical Requirements

Voltage	Amp	Phase	Hz
120 VAC	10	1	60
220 VAC	5	1	50/60

**Specifications subject to change without notice.

