KR840R Roller Registration

Accurately register a wide range of product efficiently and conveniently. Use with inkjet printing systems, labeling, card attaching, and other lines. Integrated controls allow for easy speed matching, stopping and starting with a Kirk-Rudy base.

- Moveable table
- Right or left hand justified
- Micro adjustments
- Adjustable pinch rollers

Heavy dutyPortable

✓ Easy set-up





www.kirkrudy.com

KR840R Roller Registration

Accurately register a wide range of product

FEATURES:

- Justify product right or left
- Hand crank moveable table
- Micro adjustments
- Adjustable pinch rollers
- Easy belt changes

OPTIONS:

- Stand-alone controls
- Wide version available



**** General Specifications**

Product Capacity

Width	Min 3″ (7.6 cm)	Max 17" (43.2 cm)
Length	Min 3" (7.6 cm)	Max 18" (45.7 cm)
Thickness	Min .004″ (.18 mm)	Max .25" (6.35 mm)

Operating Speeds

variable to 500 leet per minute	Maximum	Variable to 500 feet per minute
---------------------------------	---------	---------------------------------

Note: Speeds are dependent on material being fed



Physical	English	Metric
Length	24″	61 cm
Width	39.50″	100.3 cm
Height	49.25″	125.1 cm
Weight	250 lbs.	113.4 kg.

Electrical Requirements

Voltage	Amp	Phase	Hz
120 VAC	10	1	60/50

**Specifications subject to change without notice.